

# Technical Data Sheet

Sealed Air

Company: SealedAir Verpackungen GmbH

Address: Ernst-Diegel Strasse 2

Post Code / Location: 36304 Alsfeld / Germany

Contact person: Quality Department

Email: [pc.alsfeldqualitydepartment@sealedair.com](mailto:pc.alsfeldqualitydepartment@sealedair.com)

Data Sheet Nr.	81
Product Description	Mail Lite Tuff
SAP Number	Klicken oder tippen Sie hier, um Text einzugeben.
Certificated Norm	Din 53455

Characteristic	Unit	
Composition	Text	2 sites white polymate film with min. 30% recyceld content and 2 sites bubble film
Warehouse Temperature	°C	5°C – 50°C
Conversion Temperature	°C	5°C - 35°C
Thermal Corrosion	°C	>360°C
Bubble diameter	mm	9,5
Bubble high	mm	2,7
Tolerance height	%	Klicken oder tippen Sie hier, um Text einzugeben.
Weight Bubble Film	g/m <sup>2</sup>	46
Tolerance Weight	%	7
Adhesive of Flap	Type	Hotmelt
Pressure	Bar	> 0,35 bar
FSC Logo	Yes/No	0
EAN Code	Yes/No	1
Re-Open Tape	Yes/No	0
Outside Dimension	mm x mm	Klicken oder tippen Sie hier, um Text einzugeben.
Inside Dimensions	mm x mm	Klicken oder tippen Sie hier, um Text einzugeben.
Tolerance length/width	%	6
Middle weight Polymate Film		65



# Technical Data Sheet



Characteristic	Unit	
Tear strength across		not tested
Tear strength lengthwise		not tested
Resilience		not tested
Melt index bubble film ISO 1133 ( 190° - 2,16kg)	g / min	Klicken oder tippen Sie hier, um Text einzugeben.

## NOTE:

The data in this data sheet are meant as guideline. A legally binding effect cannot be derived from it.

Info for Mail Tuff

Mail Lite Tuff mailer are 100% recyclable

Creator	Jaeckel, Anna
Created on	08.03.2023 07:18:27
Modifier	Jaeckel, Anna
Modified	08.03.2023 07:21:18

